

Relive

HDP
High Definition Porcelain®

Glazed Porcelain Floor and Wall Tile



floridatile



Shown: 34132 8x48 Florida

The Relive^{HDP} line is contemporary living, contrasts and modern essentials. Inspired by the rich colors of reclaimed wood, Relive^{HDP} delivers the natural ambiance of real wood with the durable and technical characteristics of porcelain tile.

Offered in 4 dramatic colors created using HDP–High Definition Porcelain® printing technology, the high shade variation and graphic detail will enrich any residential or commercial space. The graphics are delivered in a large format 48" long plank that will create a striking presence in a livable, easy-to-maintain surface that is highlighted by a slight texture reminiscent of a natural wood surface. Relive^{HDP}, dress your space with style and functionality.

Relive^{HDP} glazed porcelain floor and wall tile is appropriate for all residential and commercial wall, countertop and backsplash applications, all residential and most commercial floor applications, is GREENGUARD® and Porcelain Tile Certified and meets the new DCOF AcuTest requirements to be installed in wet areas.

Shown on Front: 34112 8x48 Alaska

SHADE VARIATION



34112 Alaska



34132 Florida



34193 Montana



34123 Oregon

ALASKA





Shown: **34112 8x48** Alaska



34112 8x48
Alaska

FLORIDA





Shown: **34132 8x48** Florida



34132 8x48
Florida

MONTANA





Shown: **34193 8x48** Montana



34193 8x48
Montana



OREGON



Shown: 34123 8x48 Oregon



34123 8x48
Oregon



Shown: 34132 8x48 Florida



Typical Uses

Relive^{HDP} glazed porcelain floor and wall tile is appropriate for all residential and commercial wall, countertop and backsplash applications, all residential and most commercial floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI A137.1) for ceramic, stone and glass installation for specific usage and installation information.

This Florida Tile product will contribute to USGBC LEED points and the ANSI approved NAHB Green Building Points.

Field Tile Nominal Size ¹	Metric (cm)	Pcs./Sq Ft ²	Thickness ³
8" x 48"	20 x 121	.375	10.5mm

¹ These values may vary from lot to lot.

² These values are based on actual sizes including the grout joint.

³ May not apply to textured surfaces or tiles with uneven back patterns.

Properties (Floor)	ASTM	ANSI	Results ¹
DCOF AcuTest ²	A137.1	≥0.42	Pass
Durability Classification ³	C-1027	N/A	Class V
Glaze Hardness	Mohs Scale	N/A	7 Mohs
Break Strength	C-648	250 lbs.	Pass
Water Absorption	C-373	≤0.5%	≤0.5%

¹ These values vary from lot to lot. All test results are from independent laboratory tests.

² ANSI A137.1 standard, ceramic tiles selected for level interior spaces expected to be walked upon when wet must have a minimum wet DCOF AcuTest value of 0.42.

³ Class I Light Traffic Areas, Class II Medium Light Traffic Areas, Class III Medium Traffic Areas, Class IV Heavy Traffic Areas, Class IV+ Heavy Traffic Areas (high resistance to scratches and stains)

Color Variations

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.

V3 = Moderate Variation
 While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example, "that little bit of color" on one piece of tile may be the primary color on the next piece.

