



Shown: 2566E03B1 24x24 Silver natural

EDGE

BY [floridatile](#)

The EDGE collection from Florida Tile fuses the look of stone and cement into an extraordinarily resistant product, able to tolerate the most demanding applications. Contemporary in concept, EDGE is produced using proprietary Dual Tech technology to obtain extremely durable through body porcelain floor and wall tile. Designed to be an expansion of and coordinate with our popular Time/2.0 line, EDGE will compete for projects of the heaviest commercial traffic such as airports and shopping malls.

EDGE is available in three finishes: Natural, Polished, and Touch, making this line extremely versatile for interior or exterior, commercial or residential applications. Touch is a new finish that subtly knocks down the top high points to leave a slightly honed texture.

Rectified field tiles are available in a variety of sizes and finishes: 24x24 in natural finish; 12x24 in natural, polished, and touch; and 3.75x12 (cut) in natural and polished. All field tile, bullnose, and mosaics are available in all five colors: Snow, Cream, Silver, Taupe, and Carbon. These colors compliment the Time/2.0 hues except Taupe—an updated version of Dove that brings in more warm grays and lessens the chocolate brown tones.

EDGE through body porcelain floor and wall tile is appropriate for all residential and commercial wall, countertop and backsplash applications, all residential and most commercial floor applications. EDGE is GREENGUARD® and Porcelain Tile certified, and the natural finish meets DCOF AcuTest requirements to be installed in wet areas.

Shown on Front: 2566E03B1 24x24 Silver natural





MONS

Shown: 2566E01B1 24x24 Snow natural



2566E01B1 24x24
Snow natural



2536E01B1 12x24
2513E01B1 3.75x12
Snow natural



2533E01/M122
Snow mosaic natural



2536E0161 12x24
2513E0161 3.75x12
Snow polished



2536E01T1 12x24
Snow touch



CREAM

Shown: 2536E02B1 12x24 Cream natural, 2533E02/M122 Cream mosaic natural, 2536E0261 12x24 Cream polished



2566E02B1 24x24
Cream natural



2536E02B1 12x24
2513E02B1 3.75x12
Cream natural



2533E02/M122
Cream mosaic natural



2536E0261 12x24
2513E0261 3.75x12
Cream polished



2536E02T1 12x24
Cream touch



SILVER


Shown: 2566E03B1 24x24 Silver natural



2566E03B1 24x24
Silver natural



2536E03B1 12x24
2513E03B1 3.75x12
Silver natural



2533E03/M122
Silver mosaic natural



2536E0361 12x24
2513E0361 3.75x12
Silver polished



2536E03T1 12x24
Silver touch




Shown: 2536E0461 12x24 Taupe polished, 2566E04B1 24x24 Taupe natural



2566E04B1 24x24
Taupe natural



2536E04B1 12x24
2513E04B1 3.75x12
Taupe natural



2533E04/M122
Taupe mosaic natural



2536E0461 12x24
2513E0461 3.75x12
Taupe polished



2536E04T1 12x24
Taupe touch



CARBON


Shown: 2536E05T1 12x24 Carbon touch




2566E05B1 24x24
Carbon natural



2536E05B1 12x24
2513E05B1 3.75x12
Carbon natural



2533E05/M122
Carbon mosaic natural



2536E0561 12x24
2513E0561 3.75x12
Carbon polished



2536E05T1 12x24
Carbon touch



Shown: 2536E02T1 12x24 Cream touch

EDGE

BY **floridatile**

Typical Uses

EDGE through body porcelain floor and wall tile is appropriate for all residential and commercial wall, countertop and backsplash applications, all residential and most commercial floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI A137.1) for ceramic, stone and glass installation for specific usage and installation information.


This Florida Tile product will contribute to USGBC LEED points and the ANSI approved NAHB Green Building Points.

Properties (Floor)	ASTM	ANSI	Results ¹
DCOF AcuTest ²	A137.1	≥0.42	Pass (natural finish only)
Glaze Hardness	Mohs Scale	N/A	7 Mohs
Break Strength	C-648	250 lbs.	Pass
Water Absorption	C-373	≤0.5%	≤0.5%

¹ These tests are performed by a 3rd party testing lab using industry standard equipment and techniques. Values are offered in good faith as being accurate and typical of normal production. Due to the natural variation of raw materials and manufacturing processes, the values of the purchased product for any particular installation may vary.
² ANSI A137.1 standard, ceramic tiles selected for level interior spaces expected to be walked upon when wet must have a minimum wet DCOF AcuTest value of 0.42.


Field Tile Nominal Size ¹	Finish	Metric (cm)	Pcs./Sq Ft ²	Thickness ³
12" x 24"	Touch	30 x 60	.5	10.5mm
24" x 24"	Natural	60 x 60	.25	10.5mm
12" x 24"	Natural	30 x 60	.5	10.5mm
3.75" x 12"	Natural	9.5 x 30	3.25	10.5mm
12" x 24"	Polished	30 x 60	.5	10mm
3.75" x 12"	Polished	9.5 x 30	3.25	10mm

¹ These values may vary from lot to lot.
² These values are based on actual sizes including the grout joint.
³ May not apply to textured surfaces or tiles with uneven back patterns.

Trim	Shape	SKU	Nominal Size	Metric (cm)
Bullnose (Natural & Polished)		P43N9	3" x 24"	7.5 x 60

Color Variations

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.



V2 = Slight Variation

Clearly distinguishable differences in texture and/or pattern with similar colors.



floridatile